



ELEANOR

Product description

- Edgelit panel for direct recessed mount and surface or suspended mount with accessories
- Two luminous flux range variants 2,900 or 3,900 lm
- For suspended ceiling grid measure of 600 mm
- Product colour (frame) RAL 9003
- IK02
- Efficacy of the module up to 116 lm/W
- High colour rendering index CRI > 80
- Small colour tolerance (MacAdam 4) 1
- **UGR < 19**
- Small luminous flux tolerances
- Colour temperatures 3,000, 4,000 and 6,500 K
- Diffusor material standard article: PS, diffusor material **TPA article: PC**
- Lightguide material: PMMA
- Long life-time: 50,000 hours
- 5-year guarantee
- Dali, DSI, Switch Dim, 1-10v & other dimming options
- Self-Test and Dali EMPRO options

Dimensions

595mm x595mm

Technical data

Beam characteristic	90°
Ambient temperature range	-20 ... +40 °C
tp rated	45 °C
tc	70 °C
Irated	800 mA
I _{max}	900 mA
Max. permissible LF current ripple	1,170 mA
Max. permissible peak current	1,500 mA / max. 10 ms
Max. working voltage for insulation SELV	60 V
Insulation test voltage	0.5 kV
ESD classification	Severity level 2
Risk group (EN 62471:2008) ²	RG0
Classification acc. to IEC 62031	Independent
Type of protection	IP20
Lumen maintenance L70B50	50,000 h
Guarantee	5 years



Option 1	
ELATG228W	ELEANOR TPA GENERATION-2 UGR19 28W, 2900LM
ELATG136W	ELEANOR TPA GENERATION-2 UGR19 36W, 3900LM
Option 2	
4K	Colour 4000K
3K	Colour 3000K
Option 3	
-01	LED MAINS
-05	C/W 3HR EMERGENCY

Ordering Part no. Format -

Option1Option2Option3: ELATG236W4K-05 - ELEANOR TPA UGR19, 36W, 4K C/W EMERGENCY

*Other dimming options available e.g. DALI, DSI, SWITCH DIM, 1-10V AND PHASE DIM

*Emergency options available - SELF TEST and DALI EMPRO

