

STRONG-ARM LED

A high quality luminaire with clean lines, vandal resistant and tested to BSEN60529:1992 and A2: 2013. On correct installation the **Strong-Arm** luminaire can attain Anti Ligature status, tested to the requirement of the National Offenders Management Services.



FEATURES

- Flat opal polycarbonate material as standard
- Manufactured from mild steel
- Rated to IP65 & IK10
- Available with night light function
- Range of outputs available

IK10

IP65


T5
EQUIVALENT

5 YEAR
WARRANTY

TECHNICAL DETAILS

Part Number	Description	Replaces	Weight (kg)	No. Per 10A Breaker	Inrush Current (A)	Circuit Watts (W)	Board Lumens	Luminaire Lumens	Ll/cw
STR2-22W4KWH-01	22W 718mm Single Luminaire	1 x 18WT8	6.5	65	8A 80µs	22	3815	2480	112.7
STR3-31W4KWH-01	31W 1020mm Single Luminaire	1 x 30WT8	9.3	50	5A 37µs	31	5376	3495	112.7
STR4-32W4KWH-01	32W 1325mm Single Luminaire	1 x 36WT8	12.2	35	5A 37µs	32	5550	3607	112.7
STR4-44W4KWH-01	44W 1325mm Single Luminaire	2 x 36WT8	12.2	35	5A 37µs	44	7631	4960	112.7
STR5-38W4KWH-01	38W 1623mm Single Luminaire	1 x 58WT8	13.8	35	5A 37µs	38	6590	4284	112.7
STR5-44W4KWH-01	44W 1623mm Single Luminaire	2 x 58WT8	13.8	25	15A 50µs	44	7631	4960	112.7
STR6-48W4KWH-01	48W 1910mm Single Luminaire	1 x 72WT8	16.2	25	15A 50µs	48	8325	5411	112.7
STR6-68W4KWH-01	68W 1910mm Single Luminaire	2 x 72WT8	16.2	25	15A 50µs	68	11793	7666	112.7

KEY FEATURES



Part Number	Length	Width
STR2C-11W4KWH-01	718	265
STR3C-22W4KWH-01	1020	265
STR4C-22W4KWH-01	1325	265
STR5C-33W4KWH-01	1623	265
STR6C-33W4KWH-01	1910	265
STR2C-22W4KWH-01	718	265
STR3C-44W4KWH-01	1020	265
STR4C-44W4KWH-01	1325	265
STR5C-66W4KWH-01	1623	265
STR6C-66W4KWH-01	1920	265

Options

- 05** Integral Emergency (1W)
- 05ST** Integral Emergency Self Test (1W)
- DD** SwitchDIM/DALI
- WL** Wireless Control System
- WLEM** Wireless Monitored Emergency
- SL** Silver
- BL** Black
- 3K** 3000K Colour Temperature
- 5K** 5000K Colour Temperature

PHOTOMETRIC AND DIMENSION

