



AZURE-2

A range of traditional style LED battens made with LED boards. These battens offer a practical and reliable solution to replace traditional fluorescent battens. Ideal for use in commercial and retail applications where energy saving and aesthetics are important.

Features

- 5 year warranty
- CRI > 80
- 120 degree beam angle
- 125lm per circuit watt
- Dimmable and Emergency versions available upon request
- Multiple colour renderings controlled by dip switch - 3000K/4000K/6000K

Dimensions

4FT	1170x61x71mm
5FT	1470x61x71mm
6FT	1734x61x71mm



Option 1	
AZ2/4/20W	AZURE-2 4FT 20W , 3K/4K/6K ,2300LM/2400LM/2500LM
AZ2/4/40W	AZURE-2 4FT 40W , 3K/4K/6K ,4600LM/4700LM/4800LM
AZ2/5/30W	AZURE-2 5FT 30W , 3K/4K/6K ,3450LM/3550LM/3650LM
AZ2/5/60W	AZURE-2 5FT 60W , 3K/4K/6K ,6900LM/7000LM/7100LM
AZ2/6/40W	AZURE-2 6FT 40W , 3K/4K/6K ,4600LM/4700LM/4800LM
AZ2/6/65W	AZURE-2 6FT 65W , 3K/4K/6K ,7475LM/7575LM/7675LM
Option 2	
-01	LED Standard
-02R	c/w Remote Microwave (end mount)
-03	c/w Corridor Function
-04R	c/w Remote Microwave (end mount) & Corridor Function
-05	c/w Emergency M3
-06R	c/w Emergency & Remote Microwave (end mount)
-07	c/w Emergency & Corridor Function
-08R	c/w Emergency, Remote Microwave (end mount) & Corridor Function

Ordering Part no. Format -

Option1Option2: AZ2/5/30W-05 - AZURE-2 5FT 30W, 3K/4K/6K C/W EMERGENCY

***Other dimming options available** e.g. DALI, DSI, SWITCH DIM, 1-10V and Phase Dim

***Emergency options available** - Self Test and DALI EMPRO

