



VESPER-3 multiple output non corrosive luminaire

IP66 Anti corrosive Twin and Single output via dip switch, see table below :

Part Code	Description	Power (W)	Output Current (mA)	Lumen Output (lm)
VS3/4/4K-01	VESPER-3 4FT	24W	200mA	3300 lm
		30W	250mA	4000 lm
		36W	300mA	4700 lm
		42W	350mA	5380 lm
VS3/5/4K-01	VESPER-3 5FT	31W	200mA	4500 lm
		40W	250mA	5500 lm
		48W	300mA	6400 lm
		56W	350mA	7470 lm

Options

- Emergency self test option available
 - Dali & other dimming options available
 - Available with integral Microwave sensor
- *Please contact our sales office for other options*

Applications

- Suitable for a wide range of commercial applications including car parks or **24hr lighting with the 100% to 10% feature** , gymnasiums, warehouses, factories etc.

Dimensions

VS3/4 (Vesper-3 4ft)	1220mm x 100mm x 83mm
VS3/5 (Vesper-3 5ft)	1560mm x 100mm x 83mm

Features

- Multiple wattages (selectable via dip switch)
- IP66 & IK10 rated LED non corrosive
- Colour Temperature - 4000K, CRI - >80
- Polycarbonate housing and diffuser
- Philips flicker free driver
- Stainless Steel Clips
- -20°C ~ +35°C (mains fittings only)
- 5 year warranty, (including battery on certain lithium battery models. Check with sales team)
- Body Colour - RAL 7035 (grey)
- Beam Angle - 120°
- Power Factor - >0.90
- SDCM: <3
- L70B50 (50,000hours)
- Product Lifetime: 50,000hours

Option 1	
VS3/4/4K	VESPER-3 4FT 4K, 24W-42W,200mA/250mA/300mA/350mA- 3300/4000/4700/5380LM
VS3/4A/4K	VESPER-3 4FT 4K, 24W 3300LM-DALI
VS3/4B/4K	VESPER-3 4FT 4K, 30W 4000LM-DALI
VS3/4C/4K	VESPER-3 4FT 4K, 36W 4700LM-DALI
VS3/4D/4K	VESPER-3 4FT 4K, 42W 5380LM-DALI
VS3/5/4K	VESPER-3 5FT 4K, 31W-56W,200mA/250mA/300mA/350mA- 4500/5500/6400/7470LM
VS3/5A/4K	VESPER-3 5FT 4K, 31W 4500LM-DALI
VS3/5B/4K	VESPER-3 5FT 4K, 40W 5500LM-DALI
VS3/5C/4K	VESPER-3 5FT 4K, 48W 6400LM-DALI
VS3/5D/4K	VESPER-3 5FT 4K, 56W 7470LM-DALI
Option 2	
-01	LED Mains
-02	c/w Integral Microwave sensor
-03	c/w Corridor function
-04	c/w Integral Microwave sensor & Corridor function
-Y05	c/w Self Test Lithium emergency
-Z05	c/w Lithium emergency
-Y06	c/w Self Test Lithium emergency & Integral Microwave sensor
-Z06	c/w Lithium emergency & Integral Microwave sensor
-Y07	c/w Self Test Lithium emergency & Corridor function
-Z07	c/w Lithium emergency & Corridor function
-Y08	c/w Self Test Lithium emergency, Integral Microwave sensor & Corridor function
-Z08	c/w Lithium emergency, Integral Microwave sensor & Corridor function

Ordering Part no. Format :-

Option1-Option2

Example: VS3/4/4K-Z05 - Vesper-3 4ft 4K c/w Lithium emergency

**Please contact our sales office for Dimming & other options*