



## AC42CCT

CCT switchable between 3000K, 4000K & 6500K. Tough exterior provides an IP65 and IK08 housing protecting the LED components inside. 304 stainless steel clips for high corrosion resistance and anti-tamper screws for vandal proofing. Unique gear tray slots that allow us to easily integrate third party control gear for your project. Safety tether cable to gear tray enables fast installation. Compression cable gland included in fixings kit. BESA mounting kit available.

### FEATURES

IK rating	IK08
IP rating	IP65
Colour flexibility	Colour switchable
Sensor	Available on request
Dimmable	DALI2 available
Input	220-240V 50/60Hz
LED Lifetime	50,000h L70
CRI	>80Ra
SDCM	4SDCM
Emergency version available	Yes

### INSTALLATION INFORMATION

Install Connector Type	Loop in / Loop out
Inrush Current	30A, 0.3ms
Construction Material	Anti-UV Polycarbonate
Maximum ambient temperature	-20°C to 40°C
SELV	Yes
Building regulations	Part P
Electric Class (1, 2, 3)	1

### Dimensions:

1245mm x 93mm x 80mm

Product Code	Description	Colour	Beam Angle	Lm
AC42CCT/36W-01	36W Anti-Corrosive Standard	3K/4K/6.5K	120°	4140/4500/4680LM
AC52CCT/36WZ-05	36W Anti-Corrosive Lithium Emergency	3K/4K/6.5K	120°	4140/4500/4680LM

\*Please speak to our sales team for other options