



AZURE-3

A range of traditional style LED battens made with LED boards. These battens offer a practical and reliable solution to replace traditional fluorescent battens. Ideal for use in commercial and retail applications where energy saving and aesthetics are important.

***Dimmable and Emergency versions are available.**

Performance Data

Kelvin	4000K
Efficacy	~130Lm/W
Operating Temperature	-20°C to +45°C (0°C to 40°C for emergency)
Beam Angle	140°
Operating Hours	>50000
CRI	>85Ra
IP Rating	IP20
IK Rating	IK08
Macadam Ellipse	≤4 sdc _m
L70 B50	70,000 hours
L80 B50	50,000 hours
L90 B50	25,000 hours

Dimensions

4FT	1170x61x70mm
5FT	1470x61x70mm
6FT	1734x61x70mm

Product Data

Warranty	5 years
Applications	Interior
Certification(s)	CE, RoHS

Physical Data

Colour Finish	White
Luminaire Fixing	Surface Mounted, suspended, connected to BESA boxes
Construction Material	Steel
Diffuser Type	Polycarbonate

Electrical Data

Voltage Range	AC220-240V
Power Factor	>0.90
Inrush Current	20A
Protection Class IEC	Class I



Option 1	
AZ3/4/25W4K	AZURE-3 4FT 25W , 4K, 3251LM
AZ3/4/45W4K	AZURE-3 4FT 45W , 4K, 5853LM
AZ3/5/35W4K	AZURE-3 5FT 35W , 4K, 4552LM
AZ3/5/60W4K	AZURE-3 5FT 60W , 4K, 7803LM
AZ3/6/45W4K	AZURE-3 6FT 45W , 4K, 5852LM
AZ3/6/70W4K	AZURE-3 6FT 70W , 4K, 9103LM

Option 2	
-01	LED Standard
-02R	c/w Remote Microwave (end mount)
-03	c/w Corridor Function
-04R	c/w Remote Microwave (end mount) & Corridor Function
-Z05	c/w Lithium Emergency
-Y05	c/w Lithium Self test emergency
-Z06R	c/w Lithium emergency & Remote Microwave (end mount)
-Y06R	c/w Lithium Self test emergency & Remote Microwave (end mount)
-Z07	c/w Lithium emergency & Corridor Function
-Y07	c/w Lithium Self test emergency & Corridor Function
-Z08R	c/w Lithium emergency, Remote Microwave (end mount) & Corridor Function
-Y08R	c/w Lithium Self test emergency, Remote Microwave (end mount) & Corridor Function

Ordering Part no. Format -

Option1Option2: AZ3/5/35W4K-Z05 - AZURE-3 5FT 35W, 4K C/W LITHIUM EMERGENCY

***Other dimming options available** e.g. DALI, DSI, SWITCH DIM, 1-10V and Phase Dim

***Emergency options available** e.g. Self Test and DALI EMPRO