



BEAM

The Beam is available in 4 standard lengths, .85 Meter, 1.2 Metre, 1.5 Metre and 2.5 Metre. Direct version is suitable for surface mount or suspension and Direct/ Indirect version is suitable for suspension only. Beam is available in 3000k or 4000k and paint finished in Grey, White or Black. Other colours and finished available on request.

Features

- Extruded direct/indirect linear profile luminaire
- Typical percentage output ratio 75 : 25 for Indirect version
- Finished in RAL 9006 grey as standard
- Available in 4 standard lengths
- Delivering approx. 2200lm/3000lm per meter as standard for Direct & Indirect versions respectively
- Coloured matched, injection moulded end caps
- TPa opal lens for feature, general and visual areas
- Low glare prismatic lens available for office and LG7 compliance
- Tridonic low energy LED and driver system
- Lumen maintenance L80/F10 @ >72,000 hours
Efficacy up to 130 lm/tcW

Lumen Output for Direct

Length	Colour	Total Output (Llm) Std	Total Output (Llm) /LO	Total Output (Llm) /HO
850mm	830	1725	1175	2725
850mm	840	1825	1225	2875
1.2mtr	830	2575	1750	4100
1.2mtr	840	2725	1850	4300
1.5mtr	830	3150	2150	5000
1.5mtr	840	3325	2250	5250
2.5mtr	830	5150	3500	8175
2.5mtr	840	5425	3675	8575

Lumen Output for Direct/Indirect

Length	Colour	Total Output (Llm) Std	Total Output (Llm) /LO	Total Output (Llm) /HO
850mm	830	2350	1600	3725
850mm	840	2350	1600	3725
1.2mtr	830	3525	2400	5600
1.2mtr	840	3525	2400	5600
1.5mtr	830	4550	3075	7225
1.5mtr	840	4550	3075	7225
2.5mtr	830	7050	4775	11175
2.5mtr	840	7050	4775	11175

** Please call our sales office for order codes and options*