



GOLIATH

Features:

- 1000lm/1500lm (switchable) high lumen output
- Polycarbonate construction
- Built in easy-fit gear tray
- Available as self test
- Lithium LiFePO4 6.4V 6.6Ah battery
- IP65, IK08 rated
- Typical applications include warehouses, factories and industrial sites
- 4 year warranty (2year on battery)

Specification:

Input Voltage	220-240V
Total Wattage	4.5W (Charge mode) 10W@1500lm (Discharge mode)
Luminaire Lumens	1000lm / 1500lm
Lumens P/Watt	176.65lm/W / 165.73lm/W
LED Chips	2835 LED
LED Forward Voltage / Current	3.0-3.5V / 150mA
LED Chip Lifetime (L70)	>50,000hrs
CCT / CRI / SDCM	6500K / >80 / <6
Power Factor	>0.3
Running Current	52mA@1000lm / 50mA@1500lm
Inrush Current	12.8A/100us
Emergency Duration	3hrs
Emergency Lumens(DC status)	1083.23lm / 1587.04lm
Battery	LiFePO4 6.4V 6.6Ah
Material / Finish (RAL)	PC / RAL 9003
Class / IP / IK	Class II / IP65 / IK08
Beam Angle	135°
Glow Wire Testing (TP rating)	850° C
Installation Method	Surface
Temperature	5°C - 45°C
Warranty	4 years (battery 2 years)
Certificates	CE

Part codes	
GOL/NM3	GOLIATH 10W IP65 1500LM
GOL/NM3/ST	GOLIATH 10W IP65 1500LM SELF TEST