



MINI TUFF

IP65 & IK10 robust bulkhead, polycarbonate base & led Diffuser, suitable for a variety of applications, both external and internal.

Manufactured in the UK with Tridonic Generation 4 LED Boards and Drivers.

Features

- IP65 & IK10 rated robust bulkhead
- Polycarbonate base and diffuser
- Metal Base option
- Lumax high output, low glare diffuser
- Dali options available
- 5 year warranty
- Available with Photocell
- Ideal for surface conduit systems
- Slave, static and central battery options
- Anti tamper screws

Dimensions

Square	270mm x 270mm x 90mm
Round	305mm x 100mm



Option 1	
MTG412W30	Mini-Tuff 12W LED 3000K 1259lm
MTG412W40	Mini-Tuff 12W LED 4000K 1317lm
MTG418W30	Mini-Tuff 18W LED 3000K 1640lm
MTG418W40	Mini-Tuff 18W LED 4000K 1719lm
MTHDG412W30	Mini-Tuff Heavy Duty 12W LED 3000K 1259lm
MTHDG412W40	Mini-Tuff Heavy Duty 12W LED 4000K 1317lm
MTHDG418W30	Mini-Tuff Heavy Duty 18W LED 3000K 1640lm
MTHDG418W40	Mini-Tuff Heavy Duty 18W LED 4000K 1719lm
Option 2	
R	Round
S	Square
Option 3	
W	White Base - Opal Led Diffuser
B	Black Base - Opal Led Diffuser
Option 4	
-01	LED Standard
-02	c/w Microwave
-03	c/w Corridor Function
-04	c/w Microwave & Corridor Function
-05	c/w Emergency M3
-06	c/w Emergency & Microwave
-07	c/w Emergency & Corridor Function
-08	c/w Emergency, Microwave & Corridor Function

Ordering Part no. Format :- Option1Option2Option3Option4

Example: MTHDG412W40RW-01 Heavy Duty Metal base generation 4 12W LED Colour 4000K Round White Opal

*Other dimming options available e.g. DALI, DSI, SWITCH DIM, 1-10V and Phase Dim

*Available in other RAL colours on request.

*Emergency options available - Self Test and DALI EMPRO

*Daylight Sensing available - Automatic lighting control from unswitched feed.

Off with adequate ambient light, on at dusk - 10% with no presence, 100% with presence