



## NIMBUS



A surface mounted architectural halo bulkhead with a cast aluminium IK10 rated body, black as standard. It is designed for optimal light diffusion, ideal for decorative interior and exterior applications. Integral emergency and microwave detector options are available.

### Luminaire Output

Colour Temperature	4000K   5000K
CRI	>83 Ra
Efficacy	~85 Lm/W
Beam Angle	120°
Operating Hours	50,000
Macadam Ellipse	≤4 sdcm
L70 B50	70,000 hours
LEDs	Epistar (2-3 bin)

### Supply & Power

Voltage Range	AC220-240V
Power Factor	>0.95
Inrush Current	<60A
Running Current	700mA
Protection Class IEC	Class I
Driver	Integral
Cable entry	Back

### Features:

- Emergency options available
- Dimming options available
- Available with sensor options
- Black finish as standard, available in White as a special
- IP65 and IK10 rated
- 5 years warranty

### Overview

Applications	Interior/Exterior
Construction Material	Cast Aluminium
Diffuser Type	Opal polycarbonate-TP(a) rated
IP Rating	IP65
IK Rating	IK10
Mounting	Ceiling and wall mounted
Weight (kg)	2.50
Ambient Temperature	-20°C to +45°C (0°C to 40°C for emergency)
Warranty	5 years

\*Please speak to our sales office for part codes and options