



PATHFINDER ASYMMETRIC

Pathfinder is a robust bollard with a classic look suitable for most applications. It has a durable extruded aluminium body and polycarbonate lens providing good levels of vandal resistance.

Features :

- Selectable CCT - 3000K/4000K
- Power - 10w
- 3 year warranty
- C/W concrete fixings, J Bolts are available to order separately
- Root mount kit available
- IP65 & IK09 rated

Specification

Product Description	Pathfinder Asymmetric LED bollard
Product Code	PF/25W/F/ASY/B-01
Description	Pathfinder Asymmetric bollard, flat head, 10W 800lm, 2CCT, 1m
Input Voltage	100-240V
Total Wattage	10W
Luminaire Lumens	750lm (3000K) / 800lm (4000K)
Lumens P/Watt	≥75lm/W
LED Chips	2835 (30+30)
LED Forward Voltage / Current	3.0V / 150mA
LED Chip Lifetime (L70)	>36,000 hours
CCT / CRI / SDCM	3000K/4000K / >80 / <6
Driver	Eaglerise
Power Factor	≥0.95
Running Current	600mA
Inrush Current	20A Max
Material / Finish (RAL)	Die-cast aluminium, RAL9005 Sand
Class / IP / IK	Class I / IP65 / IK09
Beam Angle	N/A
Glow Wire Testing (TP rating)	N/A
Installation Method	Floor mounted
Temperature	-25 to 45 degree
Warranty	3 Years
Certificates	CE/UKCA