













120W MINI LED INVERTER

The STI-LED range of Mini Static Inverters has been engineered to suit LED lighting. Offering a cost effective solution to powering unmodified LED Luminaires in the event of mains failure, the unit is a pure sine wave inverter with a 230V AC output. The range is designed to comply with the latest European and British Standard BS EN 50171:2001.

Pure Sine Wave

Multi-Functional LCD Display

Overload and Short Circuity Protection



230V

IP41

1 YEAR

Additional Information

- 32 bit micro-controller
- Overload and short circuity protection
- Compatible with optional remote hold off relays
- Specifically designed for use with LED luminaires
- Steel housing
- Designed in accordance with BS 5266
- 3 hour emergency duration
- Wall mount or free standing
- One fused output
- Additional fused outputs available on request

INPUT CHARACTERISTICS

| Input Voltage: | 230V AC +/-10% | |
|-------------------------------|----------------|--|
| Frequency: | 50Hz | |
| Efficiency at 100% Load: >95% | | |

OUTPUT CHARACTERISTICS

| Output Voltage: | 230AC | | |
|-----------------------|----------------------|--|--|
| Output Regulation: | 1-5% Dependent on Lo | | |
| Output Frequency: | 50Hz | | |
| Number of Outputs: | 4 | | |
| Maintained: | 1 (switched live) | | |
| Continuous Overload | 1 | | |
| Capacity: | 120% | | |
| Output: | Pure Sine wave | | |
| Efficiency (100% load |): <95% | | |
| Change Over | 0.05 Seconds | | |
| Time: Output | Fuse | | |
| Protection: | | | |
| | | | |

GENERAL

| GENERAL | | | |
|-----------------------------|--------------------|--|--|
| Display Type: | LCD | | |
| Inverter Weight: | 16.5Kg | | |
| Cabinet Colour: | Grey | | |
| IP Rating: | IP41 | | |
| Altitude: | <1000m | | |
| Ambient Temperature: 0-25°C | | | |
| Relative Humidity: | 90% Non-Condensing | | |
| Acoustic Noise: | 20dBA at 1m | | |
| Ventilation: | Forced Air | | |
| | | | |

BATTERIES (one battery cabinet)

| Туре: | Sealed Lead Acid | | |
|----------------------|------------------|--|--|
| Design life: | 10 years | | |
| Duration: | 3 Hours | | |
| Voltage: | 12V | | |
| Battery Pack Weight: | 24.1kg | | |

ad DIMENSIONS

INVERTER CUBICLE

| 305mm | |
|--------------------------|--|
| 472mm | |
| 166mm | |
| Wall Mount/Free Standing | |
| Top/Side | |
| 472mm | |
| | |

BATTERY CABINETS

| Height: | 238mm |
|-------------------|--------------------------|
| Width: | 472mm |
| Depth: | 174mm |
| Fixing Locations: | Wall Mount/Free Standing |
| Cable Entry: | Top/Side |
| Door Clearances: | 472mm |

| Product Code | Output Power | Maximum Input Current | Battery Voltage | Inverter Cubicle Weight | Battery Cabinet Weight |
|--------------|--------------|-----------------------|-----------------|-------------------------|------------------------|
| STI-LED-120 | 120W | <3.0A | 12V/12Ah | 16.5Kg | 24.1Kg |