













# **400W MINI LED INVERTER**

The STI-LED range of Mini Static Inverters has been engineered to suit LED lighting. Offering a cost effective solution to powering unmodified LED Luminaires in the event of mains failure, the unit is a pure sine wave inverter with a 230V AC output. The range is designed to comply with the latest European and British Standard BS EN 50171:2001.

Pure Sine Wave

Multi-Functional LCD Display

Overload and Short Circuity Protection



230V

**IP41** 

1 YEAR

#### Additional Information

- 32 bit micro-controller
- Overload and short circuity protection
- Compatible with optional remote hold off relays
- Specifically designed for use with LED luminaires
- Steel housing
- Designed in accordance with BS 5266
- 3 hour emergency duration
- Wall mount or free standing
- One fused output
- Additional fused outputs available on request

#### INPUT CHARACTERISTICS

Input Voltage:	230V AC +/-10%		
Frequency:	50Hz		
Efficiency at 100% Load: >95%			

### **OUTPUT CHARACTERISTICS**

0 1/1				
Output Voltage:	230AC			
Output Regulation:	1-5% Dependent on Loa			
Output Frequency:	50Hz			
Number of Outputs:	4			
Maintained:	1 (switched live)			
Continuous Overload				
Capacity:	120%			
Output:	Pure Sine wave			
Efficiency (100% load	): <95%			
Change Over	0.05 Seconds			
Time: Output	Fuse			
Protection:				

#### GENIERAL

GENERAL	
Display Type:	LCD
Inverter Weight:	16.5Kg
Cabinet Colour:	Grey
IP Rating:	IP41
Altitude:	<1000m
Ambient Temperat	ure: 0-25°C
Relative Humidity:	90% Non-Condensing
Acoustic Noise:	20dBA at 1m
Ventilation:	Forced Air

# BATTERIES (two battery cabinet)

Туре:	Sealed Lead Acid
Design life:	10 years
Duration:	3 Hours
Voltage:	12V
Battery Pack Weight:	34.5Kg x 2

## ad **DIMENSIONS**

## **INVERTER CUBICLE**

305mm
472mm
166mm
Wall Mount/Free Standing
Top/Side
472mm

#### **BATTERY CABINETS**

Height:	238mm x 2		
Width:	472mm		
Depth:	174mm		
Fixing Locations:	Wall Mount/Free Standing		
Cable Entry:	Top/Side		
Door Clearances:	472mm		

Product Code	Output Power	Maximum Input Current	Battery Voltage	Inverter Cubicle Weight	Battery Cabinet Weight
STI-LED-400	400W	<5.0A	12V/36Ah	16.5Kg	35Kg x 2