



TS/LED/IP65/HO

The **TS/LED/IP65/HO** projector luminaires offer simple and effective emergency lighting from high efficiency LED projectors and suitable for exterior locations.

The **TS/LED/IP65/HO** units feature a novel lens system offering fine optical control resulting in high intensity beam patterns to ensure effective area illumination.

The 6Watt projector heads provide excellent performance and full photometry (LDT files) can be supplied upon request. The **TS/LED/IP65/HO** units are supplied with high quality 7.2Volt 4.5Ah NiCd batteries.

OPERATION

The **TS/LED/IP65/HO** units are supplied as standard with Non-maintained operation and utilise a GRP main enclosure with cast aluminium heads and Polycarbonate lenses. The 2 x 6Watt **TS/LED/IP65/HO** provides 3 hour duration from the integral Nickel Cadmium (NiCd) batteries and fully complies with the requirements of EN60598.2.22

DALI/Self-Test Options:

The **TS/LED/IP65/HO** luminaires can be specified with integral DALI/Self-Test gear providing automatic Self-Test in accordance with BSEN62034 or fully interoperable DALI operation when connected to a DALI control system.

Specification

Light source	Two 6W LED heads
Colour temperature	5000K
Light output	2 x 475lm
IP Rating	IP65
Ambient temperature (Ta)	25°C
Insulation Class	Class I
Supply	230V~ 50Hz
Supply power	5W (max.)
Charge power (typical)	2W
Weight	3.6kg (max.)

Part code	Description
TS/LED/IP65/HO	LED non-maintained with 3 hour duration
OPTIONS:	
/DALI	DALI/Self-Test version