



## VANGUARD

Slim profile surface mounted luminaire. Aluminium body with captive opal or prismatic diffuser. Secured by 4 x Torx security screws. Anti ligature when installed with 'Anti-Pick' mastic.

### Features

- Anti Ligature Surface IP44 (IP65 Gasket option)
- IK10 rated
- Available in two sizes- 410mm & 520mm
- Clear prismatic or Opal polycarbonate diffuser option
- Optional Night Light feature available
- Emergency, Microwave and Dimming option
- Stainless Steel security screws
- 5 year warranty

### Dimensions

VG4	410mm x 90mm
VG5	520mm x 140mm

## Option 1

VG4G412W30WH	Vanguard, 410mm, 12W LED 3000K, White, 1150lm
VG4G412W40WH	Vanguard, 410mm, 12W LED 4000K, White, 1280lm
VG4G418W30WH	Vanguard, 410mm, 18W LED 3000K, White, 1580lm
VG4G418W40WH	Vanguard, 410mm, 18W LED 4000K, White, 1751lm
VG4G422W30WH	Vanguard, 410mm, 22W LED 3000K, White, 2210lm
VG4G422W40WH	Vanguard, 410mm, 22W LED 4000K, White, 2300lm
VG5G422W30WH	Vanguard, 520mm, 22W LED 3000K, White, 2210lm
VG5G422W40WH	Vanguard, 520mm, 22W LED 4000K, White, 2300lm
VG5G431W30WH	Vanguard, 520mm, 31W LED 3000K, White, 3162lm
VG5G431W40WH	Vanguard, 520mm, 31W LED 4000K, White 3500lm

## Option 2

-01	LED Standard
-02	c/w Microwave
-03	c/w Corridor Function
-04	c/w Microwave & Corridor Function
-05	c/w Emergency M3
-06	c/w Emergency & Microwave
-07	c/w Emergency & Corridor Function
-08	c/w Emergency, Microwave & Corridor Function
-19	c/w Night Light
-20	c/w Night Light & Emergency

### Ordering Part no. Format :-

Option1Option2

### Example:

VG4G312W40WH-02 - Vanguard 450mm 12w Led Col 4000K c/w Microwave

*\*Please contact our sales office for dimming and other options*