















The WAYOUT exit sign range has been developed to provide a robust but attractive solution for exterior applications requiring effective safety signage. WAYOUT signs offer an excellent viewing distance of 36metres via easy to change legends, a robust polycarbonate housing with ratings of **IP65/IK08**.

The WAYOUT Exit Sign features a robust polycarbonate enclosure and is supplied with 'clip- in' safety sign legend screens behind a clear cover. It also benefits from being supplied with a mounting bracket allowing ceiling or 'flagpost' wall installation options to the standard wall mount (single sided only).

The integral rechargeable batteries and charger/driver PCB are mounted in the central housing and the advanced wide angle white LEDs provide even and effective illuminance across the legend.

Cable entries are provided into the back (single sided), top, and one side.

The Wayout range is supplied as permanently Maintained operation as standard providing 3 hour duration using long-life Lithium Iron Phosphate batteries (LiFePO4).

The luminaires are designed to fully comply with the relevant parts of ${\sf EN60598.2.22}$

DALI / Self-Test Options:

The **Wayout** LED luminaires are supplied with integral Self-Test gear complying with BSEN62034. There is also a fully interoperable DALI version available.

Note: The addition of DALI gear can create a slight shadow on one edge of the legend plate.

Features:

LED Exit Sign
15 x white LEDs
N/A
Polycarbonate housing and double diffuser plus internal 'clip-in' safety legend screen
Integral to base
329mm (L) x 226mm (W) x 66mm (H)
20mm knock-outs top, back and one end
Wall mount (single sided only); Ceiling mount bracket; 'Flagpost' wall mount bracket – (bracket supplied)



Order Code	
WAYO/M3/IP65/ST	WAYOUT IP65 SELF TEST C/W LEGENDS (ISO & EC type) & BRACKETS (WALL, CEILING & FLAG MOUNT)
WAYO/M3/IP65/DA	WAYOUT IP65 DALI C/W LEGENDS (ISO & EC type) & BRACKETS (WALL, CEILING & FLAG MOUNT)