



## ZALEX

Zalex is a high quality led plate for use in new bulkhead luminaires or for upgrading existing fittings from CFL to LED.

Zalex will consume up to 50% less energy compared to 2D Lamps with a better light output.

Zalex has a life of 50,000 hours with a five year warranty on the LED plate and driver. Certain emergency models are available with a 8 year battery warranty .

### Features:

- Dali, 1-10V, DSI Dim, Switch Dim, Phase Dim options
- Emergency models available with a 8 year battery warranty
- LED upgrade plate
- 5 year system guarantee
- Upgrade 16, 28, 38 and 55 Watt 2D lamps
- Up to 4,440 board lumens
- Colour 3000k and 4000k
- Corridor function option
- Available with Microwave Sensor / PIR
- Available with Night light
- Central battery versions available

### Dimensions:

ZXG512 / ZXG515 On geartray	215mm x 195mm x 40mm (fixing centres - 200mm)
ZXG521 / ZXG528 On geartray	320mm x 240mm x 40mm (fixing centres - 305mm)
ZXG512L / ZXG515L On geartray	320mm x 240mm x 40mm (fixing centres - 305mm)



LED LIGHTING

EMERGENCY LIGHTING

LIGHTING CONTROLS

LIGHTING COMPONENTS

EXTERIOR LIGHTS

SOLAR LIGHTING

Option 1	
ZXG512W30	ZALEX GT 12W LED COLOUR 830 1558LM
ZXG512W40	ZALEX GT 12W LED COLOUR 840 1630LM
ZXG515W30	ZALEX GT 15W LED COLOUR 830 2140LM
ZXG515W40	ZALEX GT 15W LED COLOUR 840 2261LM
ZXG521W30	ZALEX GT 21W LED COLOUR 830 3060LM
ZXG521W40	ZALEX GT 21W LED COLOUR 840 3220LM
ZXG528W30	ZALEX GT 28W LED COLOUR 830 4233LM
ZXG528W40	ZALEX GT 28W LED COLOUR 840 4440LM
Option 2	
01	LED Standard
02	c/w Microwave
03	c/w Corridor Function
04	c/w Microwave & Corridor Function
05	c/w Emergency M3
06	c/w Emergency & Microwave
07	c/w Emergency & Corridor Function
08	c/w Emergency, Microwave & Corridor Function
09	c/w Dali Mains
10	c/w Dali Mains & Dali Emergency
11	c/w Dali Mains & Standard Emergency
12	c/w Standard Mains & Dali Emergency
13	c/w Dali Mains & Self test Emergency

### Ordering Part no. Format :-

Option1-Option2

### Example:

ZXG512W830-02 - Zalex 12w LED Col 830 c/w Microwave

\*Emergency options available - Self Test and DALI EMPRO

\*Daylight Sensing available - Automatic lighting control from unswitched feed.

Off with adequate ambient light, on at dusk - 10% with no presence, 100% with presence