

5 YR WARRANTY

FIRE RATED

IP65

DIM

100 LM/W

TP(a)

TESTED WITH I-JOIST CEILINGS


## FLAME

Fire rated downlight (30/60/90 min), tested with I-joint ceilings. **Flame** is switchable 3000K or 4000K via a dip switch at the front (behind bezel) and has an IP65 front. **Flame** comes with an integrated dimmable driver and interchangeable bezels as optional.

### Overview

Applications	Interior
Construction Material	Aluminium
Diffuser Type	Polycarbonate-TP(a) rated
IP Rating	IP65
IK Rating	IK08
Mounting	Recessed
Weight (kg)	0.2
Ambient Temperature	-20°C to +45°C
Warranty	5 years

### Photometry



### Luminaire Output

Colour Temperature	Switchable 3000K   4000K
CRI	>80 Ra
Efficacy	~100 Lm/W
Beam Angle	60°
Operating Hours	50,000
Macadam Ellipse	≤6 sdcm
L70 B50	50,000 hours

### Supply & Power

Wattage	6W
Voltage Range	AC220-240V
Power Factor	>0.90
Inrush Current	<30A
Running Current	DC71mA
Protection Class IEC	Class II
Driver	Integral dimmable
Cable entry	Back
6A Type B Breaker	200 downlights
10A Type B Breaker	350 downlights

**Order code**

FLA/6W/CCT	FLAME 6W IP65 FIRE RATED DOWNLIGHT, 602LM, 3K/4K
------------	--

**Optional**

FLA/BEZ/CH	FLAME CHROME BEZEL
FLA/BEZ/BCH	FLAME BRUSHED CHROME BEZEL
FLA/BEZ/BLK	FLAME BLACK BEZEL
CT101C	3 PIN PLUG/SOCKET



CT101C

